

Samsung V-NAND SSD 970 EVO Plus

2021 Data Sheet

Revision 3.0



LEGAL DISCLAIMER

SAMSUNG ELECTRONICS CO., LTD. RESERVES THE RIGHT TO CHANGE PRODUCTS, INFORMATION AND SPECIFICATIONS WITHOUT NOTICE.

Products and specifications discussed herein are provided for reference purposes only. All information discussed herein may change without notice and is provided on an "AS IS" basis, without warranties of any kind. This document and all information discussed herein remain the sole and exclusive property of Samsung Electronics Co., Ltd. No license of any patent, copyright, mask work, trademark or any other intellectual property right is granted under this document, by implication, estoppels or otherwise. Samsung products are not intended for use in life support, critical care, medical, safety equipment, or similar applications where product failure could result in loss of life or personal or physical harm, or any military or defense application, or any governmental procurement to which special terms or provisions may apply. For updates or additional information about Samsung products, contact your nearest Samsung representative. All brand names, trademarks and registered trademarks belong to their respective owners.

COPYRIGHT © 2021

This material is copyrighted by Samsung Electronics Co., Ltd. Any unauthorized reproductions, use or disclosure of this material, or any part thereof, is strictly prohibited and is a violation under copyright law.

TRADEMARKS & SERVICE MARKS

The Samsung logo is the trademark of Samsung Electronics Co., Ltd. All other company and product names may be trademarks of the respective companies with which they are associated.

For more information, please visit www.samsung.com/ssd and www.samsungssd.com.
To download the latest software & manuals, please visit www.samsung.com/samsungssd

TECHNICAL SPECIFICATIONS

Samsung SSD 970 EVO Plus

Usage Application	Client PCs					
Interface	PCIe® Gen 3.0 x4, NVMe™ 1.3					
Hardware Information	Capacity ¹⁾	250GB	500GB	1TB	2TB	
	Controller	Samsung in-house Controller				
	NAND Flash Memory	Samsung V-NAND 3bit MLC				
	DRAM Cache Memory	512MB LPDDR4	1GB LPDDR4	2GB LPDDR4		
	Dimension	Max 80.15 x Max 22.15 x Max 2.38 (mm)				
	Form Factor	M.2 (2280) ²⁾				
Performance (Up to.) ³⁾⁴⁾	Sequential Read	3500 MB/s				
	Sequential Write	2300 MB/s	3200 MB/s	3300 MB/s		
	QD 1 Thread 1	Ran. Read	17K IOPS	19K IOPS		
		Ran. Write	60K IOPS		62K IOPS	
	QD 32 Thread 4	Ran. Read	250K IOPS	480K IOPS	600K IOPS	620K IOPS
		Ran. Write	550K IOPS			560K IOPS
Power Consumption ⁵⁾	Idle (ASPT on)		30mW			
	Active (Avg.)	Read	5 W	5.5 W		
		Write	4.2 W	5.8 W	6 W	
	L1.2 mode		5 mW			
Reliability	Temp.	Operating	0°C to 70°C (Measured by S.M.A.R.T. Temperature Proper airflow recommended)			
		Non-Operating	-45°C to 85°C			
	Humidity		5% to 95% non-condensing			
	Shock	Non-Operating	1,500G(Gravity), duration: 0.5ms, 3 axis			
	Vibration	Non-Operating	20~2,000Hz, 20G			
	MTBF		1.5 million hours			
Warranty ⁹⁾	TBW ⁶⁾⁷⁾	150TB	300TB	600TB	1200TB	
	Period	5 years limited ⁸⁾				
Supporting Features	TRIM (Required OS support), Garbage Collection, S.M.A.R.T					
Data Security	AES 256-bit Full Disk Encryption, TCG/Opal V2.0, Encrypted Drive (IEEE1667)					

- 1) 1GB = 1,000,000,000 bytes by IDEMA. A certain portion of capacity may be used for system file and maintenance use, thus the actual available capacity may differ from the labeled capacity.
- 2) M.2 is the specification of a form factor for ultra-thin PCs. The M.2 standard allows widths of 12, 16, 22 and 30mm and lengths of 16, 26, 30, 38, 42, 69, 80 and 110mm. Commercially popular M.2 are those with a width of 22mm and lengths of 30, 42, 60, 80 and 110mm. Samsung provides the most popular form factor, which is 22mm x 80mm (i.e., 2280), for the convenience of customers.
- 3) Sequential and random performance measurements are based on Iometer1.1.0. Performance may vary based on SSD's firmware version, system hardware & configuration. Test system configuration: Intel Core i7-7700K @ 4.2GHz, SAMSUNG DDR4 32GB, OS-Windows 10 Build 10240, Chipset-ASUS PRIME Z270-A.
- 4) Sequential and random write performance was measured with Intelligent TurboWrite technology being activated. Intelligent TurboWrite operates only within a specific data transfer size. Performance may vary depending on SSD's firmware, system hardware & configuration and other factors. For detailed information, please contact your local service center.
- 5) Power consumption is measured with Iometer1.1.0 version with Intel Core i7-7700K @ 4.2GHz, SAMSUNG DDR4 16GB, Gigabyte GA-Z270X, OS – Windows 10 PRO K x64.
- 6) All documented endurance test results are in compliance with JESD218 Standards. Please visit www.jedec.org for detailed information on JESD218 Standards
- 7) TBW means Terabytes Written.
- 8) Please refer to the detailed warranty statement here at <http://www.samsung.com/samsungssd>
- 9) Warranty provides coverage for the stated time period or the TBW, whichever comes first.

PRODUCT LINEUP

Density	Model Name	Box Contents	Model Code
250GB*	MZ-V7S250	Samsung SSD 970 EVO Plus 250GB Warranty Statement	MZ-V7S250BW MZ-V7S250B/AM
500GB*	MZ-V7S500	Samsung SSD 970 EVO Plus 500GB Warranty Statement	MZ-V7S500BW MZ-V7S500B/AM
1TB (1,000GB*)	MZ-V7S1T0	Samsung SSD 970 EVO Plus 1TB Warranty Statement	MZ-V7S1T0BW MZ-V7S1T0B/AM
2TB (2,000GB*)	MZ-V7S2T0	Samsung SSD 970 EVO Plus 2TB Warranty Statement	MZ-V7S2T0BW MZ-V7S2T0B/AM

* GB: 1GB = 1,000,000,000 bytes. The actual usable capacity may be less than the labeled capacity.

For more information, including but not limited to the warranty provided for this product, and to download the latest software & manuals, please visit www.samsung.com/ssd and www.samsungssd.com.

Testing Configuration and notes

Below you will find a list of system configurations Samsung used to obtain the results reported in this Data Sheet.

	Read/Write Performance	Power Consumption
Interface	PCIe® Gen 3.0 x4	PCIe® Gen 3.0 x4
OS	Windows 10 Build 10240	Windows 10 PRO K x64
CPU	Intel Core i7™ -7700K @ 4.2GHz	Intel Core i7™ -7700K @ 4.2GHz
Memory	Samsung DDR4 2,400MHz 32GB (16GB x 2ea)	Samsung DDR4 2,133MHz 16GB (8GB x 2ea)
Chipset	ASUS PRIME Z270-A	Gigabyte GA-Z270X
Test Program	IOmeter 1.1.0	IOmeter 1.1.0

Revision History

Revision Number	Description	Revision Date
1.0	Initial Release	January, 2019
2.0	Added 2TB Specification	March, 2019
3.0	The footnote 4 is fixed, the controller name is deleted	June, 2021