Samsung Portable SSD T7

2024 Data Sheet

Revision 2.0





DISCLAIMER

SAMSUNG ELECTRONICS RESERVES THE RIGHT TO CHANGE PRODUCTS, INFORMATION AND SPECIFICATIONS WITHOUT NOTICE.

Products and specifications discussed herein are for reference purposes only. All information discussed herein may change without notice and is provided on an "AS IS" basis, without warranties of any kind. This document and all information discussed herein remain the sole and exclusive property of Samsung Electronics. No license of any patent, copyright, mask work, trademark or any other intellectual property right is granted by one party to the other party under this document, by implication, estoppels or otherwise. Samsung products are not intended for use in life support, critical care, medical, safety equipment, or similar applications where product failure could result in loss of life or personal or physical harm, or any military or defense application, or any governmental procurement to which special terms or provisions may apply. For updates or additional information about Samsung products, contact your nearest Samsung office (www.samsung.com/samsungssd and www.samsung.com/support). All brand names, trademarks and registered trademarks belong to their respective owners.

COPYRIGHT © 2024

This material is copyrighted by Samsung Electronics. Any unauthorized reproductions, use or disclosure of this material, or any part thereof, is strictly prohibited and is a violation under copyright law.

SAMSUNG

Technical Specifications

Samsung Portable SSD T7						
Interface	USB 3.2 Gen 2 (10 Gbps)					
Hardware Information	Capacity ¹		1 TB	2 TB	4 TB	
	Dimensions		85 x 57 x 8 mm			
	Weight		72 grams²			
Performance	Sequential Read ³		Up to 1,050 MB/sec			
	Sequential Write ³		Up to 1,000 MB/sec			
Durability	Drop Resistant		Up to 2 m ⁴			
Cit	Encryption		AES 256-bit hardware encryption			
Security	Software		Samsung Magician Software ⁵			
	Temperature	Operating	0 °C to 60 °C ⁶			
		Non-Operating	-40 °C to 85 °C			
Reliability	Humidity		5 % to 95 % non-condensing			
	Shock	Non-Operating	1,500 G, duration: 0.5 ms, 3 axis			
	Vibration	Non-Operating		20~2,000 Hz, 20 G		
	Certifications		CE, BSMI, KC, VCCI, RCM, FCC, IC, UL, TUV, CB, EAC, UKCA, BIS			
RoHS Compliance			RoHS 2			
Warranty ⁷	Pe	eriod	Three (3) Year Limited Warranty			

SAMSUNG

 $^{1.1\,\}mathrm{GB} = 1,000,000,000\,\mathrm{bytes},\,1\,\mathrm{TB} = 1,000,000,000,000\,\mathrm{bytes}.$ Lower capacity may be demonstrated by your computer due to use of a different measurement standard.

^{2.} Exact weight of product may vary by capacity.

^{3.} Max data transfer speed is measured based on Samsung's internal testing standards with the enclosed cable. Performance may vary depending on host configuration, cable and user system environment.

^{4.} The drop test was conducted under controlled conditions. Drop resistance may vary depending on the actual environmental conditions. Damage caused by drop is not covered under warranty.

^{*} Test condition: Device was dropped free-fall to a metal plate from 2-meter height.

^{**} No warranty is provided for any physical damage.

^{5.} Samsung Magician Software compatible with Windows® 10 and higher, Mac OS® High Sierra (10.13.6) and higher, Android™ 5.1 (Lollipop) and higher

^{6.} Tc is measured at the hottest point on the case. Sufficient airflow is recommended to be operated properly on heavier workload within device operating temperature.

^{7.} Please refer to the detailed warranty statement here at https://semiconductor.samsung.com/consumer-storage/support/documents/.

PRODUCT LINE-UP

Density	Model Name	Model Code	Box Contents		
4 TB	MU-PC4T0	MU-PC4T0T/AM			
		MU-PC4T0T/WW			
2 TB	MU-PC2T0	MU-PC2T0H/AM			
		MU-PC2T0H/WW	Samsung Portable SSD T7USB Type-C to A cable		
		MU-PC2T0T/AM			
		MU-PC2T0T/WW	· USB Type-C to C cable		
1 TB	MU-PC1T0	MU-PC1T0H/AM	· Quick User Manual & Warranty Statement		
		MU-PC1T0H/WW			
		MU-PC1T0T/AM			
		MU-PC1T0T/WW			